

VTH1550CHM

IP Indoor Monitor



Features

- 7" TFT Capacitive touch screen
- IPC surveillance
- Alarm integration
- Micro SD card optional, max 32GB
- Record & Snapshot(SD card needed)



Technical Specification

Model	VTH1550CHM
-------	------------

System

Main Processor	Embedded Micro Processor
----------------	--------------------------

Operation System	Embedded LINUX OS
------------------	-------------------

Video

Video Compression	H.264
-------------------	-------

Audio

Audio Compression	G.711
-------------------	-------

Audio Input	All-direction Microphone
-------------	--------------------------

Audio Output	Built-in Loudspeaker
--------------	----------------------

Bidirectional Talk	Support Dual-way Bidirectional talk
--------------------	-------------------------------------

Display

LCD Screen	7" 800x480, Capacitive
------------	------------------------

Operation Mode

Input	Touch screen
-------	--------------

Interface

Alarm In	8
----------	---

RS485	1
-------	---

Network

Ethernet	10M/100Mbps Self-adaptive
----------	---------------------------

Network Protocol	TCP/IP
------------------	--------

General

Memory Slot	Micro SD, Max 32GB
-------------	--------------------

Installation	Flush
--------------	-------

Power	DC 12V/ supply directly by VTNS1060A
-------	--------------------------------------

Power Consumption	Standby ≤1.5W, Work ≤7W
-------------------	-------------------------


Working Temperature	-10°C~+55°C
---------------------	-------------

Relative Humidity	10%~90%RH
-------------------	-----------


Dimensions	200.5mm×136.5mm×22.0mm
------------	------------------------

Weight	1.0Kg
--------	-------

Dimensions



View Area



Application

