DATASHEET
TR-NS15061S-150-4PoE



TR-NS15061S-150-4PoE– is an unmanaged switch with 4 10/100/1000 Mbps PoE portswith the ability to power up the connected devices power twisted pair.

Basic equipment:

- Switch ..... 1pcs.
- DIN-Rail Kit ..... 1pcs.
- Datasheet ..... 1pcs.

Warranty service:

- Three - year warranty service from the date of sale.
- In case of the warranty card absence, the warranty period is determined from the date of sale.

SEC.RU | Короткий путь к информации
Скачано с sec.ru

Specification:

Model	**TR-NS15061S-150-4PoE**	
Ethernet ports	4 x 10/100/1000 Mbps (Base-T) 1 x 10/100/1000 Mbps (Base-T, RJ45) 1 x 1000 Mbps (Base-X, SFP)	
PoE Standards	Port 1: IEEE802.3af/at/bt	Ports 2-4: IEEE802.3af/at
Maximum capacity per port	Total: 150W Port 1: up to 60W	Ports 2-4: up to 30W
Power pinout via PoE	Port 1: DC+: 1/2/4/5 DC-: 3/6/7/8	Ports 2-4: DC+: 1/2 DC-: 3/6
Switching capacity	12 Gbps	
Transmission speed	8.92 Mpps	
Buffer size	2.5 MB	
MAC addresses table size	2000	
Stream management	No	
Data transmission range	Up to 250m	
Function	Autoadaptation	
PD Alive[1]	Supported. The port restarts 150 seconds after device connection loss	
Power	PoE: DC 37-57V noPoE: DC 12-57V	
Lightning protection	Standard mode 2кV Differential mode 4kV	
Electrostatic discharge protection	Air discharge 8кV Contact discharge 15kV	
Maximum power consumption	150W	
Installation	DIN-Rail	
Working temperature	-40ºC...80ºC	
Permissible humidity level	5 — 95 %	
Weight, kg	0.9	
Dimensions (W xD x H), mm	155 x 115 x 40	

[1] For more details, see the user manual for the device.

DATE OF SALE

SERIAL NUMBER

www: helpdesk.trassir.com
mail: helpdesk@trassir.com

SEC.RU | Короткий путь к информации
Скачано с sec.ru